
Product data sheet



GF Uponor Uni Pipe PLUS white 16x2,0 200m

1059577

- Coil
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier



About GF Uponor Uni Pipe PLUS white

Specification

Uponor Uni Pipe PLUS Seamless Aluminium Composite (SAC).

PE-RT/AL/PE-RT - 5 layer composite pipe consisting of an Aluminium pipe (100% oxygen-proof diffusion barrier, exceeding the requirements of DIN 4726), bonded to an inner layer of PE-RT (Polyethylene Raised Temperature), and outer layer of white PE-RT (Polyethylene Raised Temperature)
- Manufactured to BS EN ISO 21003-1 2008.
- Pipes are marked at 1m intervals with full production data in accordance with the requirements of the standard.
- Sizes 14-32 mm supplied as flexible coils
- Sizes 16-32 mm as extra rigid straight lengths.

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.


Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval
- WRAS or
- KIWA
To meet the requirements of the
Water Supply (Water Fittings) Regulations 1999

GF Uponor Uni Pipe PLUS white 16x2,0 200m

1059577



Product code

Item no EAN	4021598121256
Item no GF	35001059577
Item no GTIN	04021598121256
Item no LVI	1720138
Item no NOBB	48167238
Item no NRF	5072089
Item no RSK	2004922
Item no VVS	087480616

Dimensions

Item Unit Height	16
Item Unit Length	1000
Item Unit Weight	0,117
Item Unit Width	16
Item_UOM	m

Measurements

Length	200
Outer Diameter_do	16
Wall thickness_s	2

Packaging

Packaging GTIN PL1	06414905412105
Packaging GTIN PL4	06414905412112
Packaging Height PL1	195
Packaging Height PL4	2000
Packaging Length PL1	800
Packaging Length PL4	1200

Packaging Quantity PL1	200
Packaging Quantity PL4	2600
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,12324
Packaging Volume PL4	1,92
Packaging Weight PL1	24,744
Packaging Weight PL4	346,672
Packaging Width PL1	790
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+