


Uponor Uni Pipe PLUS white 25x2,5 50m

1059581

- Coil
- High dimensional stability, low expansion rates
- Increased flexibility
- 100% oxygen barrier



About Uponor Uni Pipe PLUS white

Specification

Uponor Uni Pipe PLUS Seamless Aluminium Composite (SAC).

PE-RT/AL/PE-RT - 5 layer composite pipe consisting of an Aluminium pipe (100% oxygen-proof diffusion barrier, exceeding the requirements of DIN 4726), bonded to an inner layer of PE-RT (Polyethylene Raised Temperature), and outer layer of white PE-RT (Polyethylene Raised Temperature)

- Manufactured to BS EN ISO 21003-1 2008.
- Pipes are marked at 1m intervals with full production data in accordance with the requirements of the standard.
- Sizes 14-32 mm supplied as flexible coils
- Sizes 16-32 mm as extra rigid straight lengths.

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Uni Pipe PLUS white 25x2,5 50m

1059581



Product code

Item no EAN	4021598121294
Item no GF	35001059581
Item no GTIN	04021598121294
Item no LVI	1720142
Item no NOBB	48167276
Item no NRF	5072094
Item no RSK	2004925
Item no VVS	087480325

Dimensions

Item Unit Height	25
Item Unit Length	1000
Item Unit Weight	0,244
Item Unit Width	25
Item_UOM	m

Measurements

Length	50
Outer Diameter_do	25
Wall thickness_s	2,5

Packaging

Packaging GTIN PL1	06414905412167
Packaging GTIN PL4	06414905412174
Packaging Height PL1	130
Packaging Height PL4	2000
Packaging Length PL1	1140
Packaging Length PL4	1140
Packaging Quantity PL1	50
Packaging Quantity PL4	700

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,168948
Packaging Volume PL4	2,5992
Packaging Weight PL1	14,316
Packaging Weight PL4	210,424
Packaging Width PL1	1140
Packaging Width PL4	1140

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb