Product data sheet



GF Uponor Renovis component pack 4-6x

1061165

- For jointing of Uponor Renovis Panels to the existing heating system
- Pack for max. 15 m² radiant heating area:
- For connection of 1 loop with 4 x 3 Renovis Panels (spread 10K) or
- For connection of 1 loop with 6 x 2 Renovis Panels (spread 5K)

- Consists on:
- 60 m Pipe PE-Xa 20x2,0 mm
- 15 pcs Rail 20 (L=250mm)
- 2 pcs Q&E Red- Coupling 20-9,9
- 10 pcs Q&E Coupling 9,9-9,9
- 15 pcs Q&E Tee 20-9,9-20
- 2 pcs Manifold connection 20-G3/4



About GF Uponor Renovis component pack

Specification

- Renovis prefab heating and cooling panel system, with embedded pipes 9.9mm.
- Based on15mm fibre-reinforced gypsum panel
- Fire class E to BS EN 13501-1
- For mounting on defined dry-build sub constructions

Application

- Ideal for new-build and rennovation projects
- Radiant wall and ceiling heating and cooling
- For dry-build installations

GF Uponor Renovis component pack 4-6x

1061165



Product code

Item no EAN	4021598121874
Item no GTIN	04021598121874

Dimensions

Item Unit Height	21
Item Unit Length	1000
Item Unit Weight	8,8
Item Unit Width	21
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905412747
Packaging GTIN PL4	06414905412754
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	10
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	8,89
Packaging Weight PL4	104
Packaging Width PL1	135
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+