


Uponor Renovis component pack 4-6x

1061165

- For jointing of Uponor Renovis Panels to the existing heating system
- Pack for max. 15 m² radiant heating area:
- For connection of 1 loop with 4 x 3 Renovis Panels (spread 10K) or
- For connection of 1 loop with 6 x 2 Renovis Panels (spread 5K)

- Consists on:

- 60 m Pipe PE-Xa 20x2,0 mm
- 15 pcs Rail 20 (L=250mm)
- 2 pcs Q&E Red- Coupling 20-9,9
- 10 pcs Q&E Coupling 9,9-9,9
- 15 pcs Q&E Tee 20-9,9-20
- 2 pcs Manifold connection 20-G3/4



About Uponor Renovis component pack

Specification


- Renovis prefab heating and cooling panel system, with embedded pipes 9.9mm.
- Based on 15mm fibre-reinforced gypsum panel
- Fire class E to BS EN 13501-1
- For mounting on defined dry-build sub constructions

Application

- Ideal for new-build and renovation projects
- Radiant wall and ceiling heating and cooling
- For dry-build installations

Uponor Renovis component pack 4-6x

1061165



Product code

Item no EAN 4021598121874

Item no GTIN 04021598121874

Dimensions

Item Unit Height 21

Item Unit Length 1000

Item Unit Weight 8,8

Item Unit Width 21

Item_UOM set

Packaging

Packaging GTIN PL1 06414905412747

Packaging GTIN PL4 06414905412754

Packaging Height PL1 89

Packaging Height PL4 678

Packaging Length PL1 176

Packaging Length PL4 1200

Packaging Quantity PL1 1

Packaging Quantity PL4 10

Packaging Type PL1 Base_Box

Packaging Type PL4 Pallet

Packaging Volume PL1 0,00211464

Packaging Volume PL4 0,65088

Packaging Weight PL1 8,89

Packaging Weight PL4 104

Packaging Width PL1 135

Packaging Width PL4 800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb