


Uponor Comfort Pipe Minitec 9,9x1,1 240m

1063289

- Material: PE-Xa



About Uponor Comfort Pipe Minitec

Specification


- Pipes manufactured from cross-linked polyethylene (PE-Xa) acc. BS EN ISO 15875
- EVOH (ethylene vinyl alcohol) layer for oxygen diffusion resistance as per DIN 4726
- Application class 4 - Underfloor heating and low temperature radiators
- Fire class E according to BS EN 13501-1.

Application

- Underfloor heating and low temperature radiators
- Max design temperature: 80°C
- Malfunction temperature 100°C
- Design pressure 6 Bar at 70°C

Uponor Comfort Pipe Minitec 9,9x1,1 240m

1063289



Product code

Item no EAN	7321500056681
Item no GF	35001063289
Item no GTIN	07321500056681
Item no LVI	2012144
Item no NOBB	50387585
Item no NRF	8361055
Item no RSK	2419975
Item no VVS	087230074

Dimensions

Item Unit Height	10
Item Unit Length	1000
Item Unit Weight	0,038
Item Unit Width	10
Item_UOM	m

Measurements

Outer Diameter_do	9,9
Wall thickness_s	1,1

Packaging

Packaging GTIN PL1	06414905413379
Packaging GTIN PL4	06414905413386
Packaging Height PL1	100
Packaging Height PL4	924
Packaging Length PL1	780
Packaging Length PL4	1200
Packaging Quantity PL1	240
Packaging Quantity PL4	2640
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,06084
Packaging Volume PL4	0,88704
Packaging Weight PL1	10,476
Packaging Weight PL4	118,6
Packaging Width PL1	780
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb