
Product data sheet



GF Uponor Comfort Pipe Minitec 9,9x1,1 240m

1063289

- Material: PE-Xa



About GF Uponor Comfort Pipe Minitec

Specification


- Pipes manufactured from cross-linked polyethylene (PE-Xa) acc. BS EN ISO 15875
- EVOH (ethylene vinyl alcohol) layer for oxygen diffusion resistance as per DIN 4726
- Application class 4 - Underfloor heating and low tempertaure radiators
- Fire class E according to BS EN 13501-1.

Application

- Underfloor heating and low tempertaure radiators
- Max design temperature: 80°C
- Malfunction temperature 100°C
- Design pressure 6 Bar at 70°C

GF Uponor Comfort Pipe Minitec 9,9x1,1 240m

1063289



Product code

Item no EAN	7321500056681
Item no GF	35001063289
Item no GTIN	07321500056681
Item no LVI	2012144
Item no NOBB	50387585
Item no NRF	8361055
Item no RSK	2419975
Item no VVS	087230074

Dimensions

Item Unit Height	10
Item Unit Length	1000
Item Unit Weight	0,038
Item Unit Width	10
Item_UOM	m

Measurements

Outer Diameter_do	9,9
Wall thickness_s	1,1

Packaging

Packaging GTIN PL1	06414905413379
Packaging GTIN PL4	06414905413386
Packaging Height PL1	804
Packaging Height PL4	950
Packaging Length PL1	788
Packaging Length PL4	1200
Packaging Material (number) PL1	20

Packaging Material PL1	corrugated cardboard / cartone
Packaging Material (short) PL1	PAP_C
Packaging Quantity PL1	240
Packaging Quantity PL4	2640
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,068424
Packaging Volume PL4	0,912
Packaging Weight PL1	10,009
Packaging Weight PL4	135,099
Packaging Width PL1	108
Packaging Width PL4	800

Technical data

Recycling Text Block PL1	corrugated cardboard / cartone

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+