


Uponor Uni Pipe PLUS white insulated S6 WLS 035 16x2,0 blue 75m

1063556

- Coil
- Insulation thickness 6 mm
- Thermal conductivity $\lambda=0,035$ W/m*k
- Round extruded
- Fire Class E to BS EN 13501-1



About Uponor Uni Pipe PLUS white insulated S6 WLS 035

Specification

Uponor Uni Pipe PLUS Seamless Aluminium Composite (SAC).

PE-RT/AL/PE-RT - 5 layer composite pipe consisting of an Aluminium pipe (100% oxygen-proof diffusion barrier, exceeding the requirements of DIN 4726), bonded to an inner layer of PE-RT (Polyethylene Raised Temperature), and outer layer of white PE-RT (Polyethylene Raised Temperature)

- Manufactured to BS EN ISO 21003-1 2008.
- Pipes are marked at 1m intervals with full production data in accordance with the requirements of the standard.
- Sizes 14-32 mm supplied as flexible coils
- Sizes 16-32 mm as extra rigid straight lengths.

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Uni Pipe PLUS white insulated S6 WLS 035 16x2,0 blue 75m

1063556



Product code

Item no EAN	4021598124462
Item no GF	35001063556
Item no GTIN	04021598124462
Item no VVS	087483116

Dimensions

Item Unit Height	28
Item Unit Length	1000
Item Unit Weight	0,138
Item Unit Width	28
Item_UOM	m

Measurements


Outer Diameter_do	16
Outer Diameter_do1	28
Wall thickness_s	2
Wall thickness_s1	6

Packaging

Packaging GTIN PL1	06414905413461
Packaging GTIN PL4	06414905413478
Packaging Height PL1	295
Packaging Height PL4	2000
Packaging Length PL1	780
Packaging Length PL4	1200
Packaging Quantity PL1	75
Packaging Quantity PL4	600
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,179478

Packaging Volume PL4	1,92
Packaging Weight PL1	10,454
Packaging Weight PL4	107,8
Packaging Width PL1	780
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb