

Uponor Wipex swivel union G11/4 120mm

1065442

- Swivel union - double nipple
- Parallel thread G" for O-ring sealing
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistance brass



About Uponor Wipex swivel union

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Wipex swivel union G11/4 120mm

1065442



Measurements

Cylindric_thread_G	1 1/4
Cylindric_thread_G1	1 1/4
LENGTH_L	120
Length (l1)	16
Length (l2)	21
z1	83

Product code

Item no EAN	4021598131071
Item no GF	35001065442
Item no GTIN	04021598131071

Dimensions

Item Unit Height	120
Item Unit Length	50
Item Unit Weight	0,663
Item Unit Width	50
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905484652
Packaging GTIN PL3	06414905484669
Packaging Height PL1	121
Packaging Height PL3	145
Packaging Length PL1	51
Packaging Length PL3	250
Packaging Quantity PL1	1
Packaging Quantity PL3	8
Packaging Type PL1	Plastic_Bag
Packaging Type PL3	Box

Packaging Volume PL1	0,000314721
Packaging Volume PL3	0,005075
Packaging Weight PL1	0,678
Packaging Weight PL3	5,49
Packaging Width PL1	51
Packaging Width PL3	140

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb