
Product data sheet



GF Uponor S-Press PLUS bend 90° 16-16

1070527

- Made of DZR brass
- Extra low pressure loss compared to an elbow type fitting



About GF Uponor S-Press PLUS bend 90°

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification

UK Reg4 approval
- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS bend 90° 16-16

1070527



Product code

Item no EAN	6414905218479
Item no GF	35001070527
Item no GTIN	06414905218479
Item no LVI	1720803
Item no NOBB	55171983
Item no NRF	5114454
Item no RSK	1896557
Item no VVS	045470216

Dimensions

Item Unit Height	47.3
Item Unit Length	47.3
Item Unit Weight	0,054
Item Unit Width	21.9
Item_UOM	pce

Measurements

Length (l1)	37
Length (l2)	37
z1	17
Z2	17

Packaging

Packaging GTIN PL1	06414905278985
Packaging GTIN PL3	06414905424948
Packaging GTIN PL4	06414905279005
Packaging Height PL1	89
Packaging Height PL3	95

Packaging Height PL4	714
Packaging Length PL1	87
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	7680
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000518781
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,56
Packaging Weight PL3	4,58
Packaging Weight PL4	463,68
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+