


Uponor S-Press PLUS coupling 25-25

1070549

- Made of tin-plated DZR brass



About Uponor S-Press PLUS coupling

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS coupling 25-25

1070549



Product code

Item no EAN	6414905218691
Item no GF	35001070549
Item no GTIN	06414905218691
Item no LVI	1720737
Item no NOBB	55172206
Item no NRF	5114478
Item no RSK	1899430
Item no VVS	045480025

Dimensions

Item Unit Height	32.3
Item Unit Length	68.2
Item Unit Weight	0,115
Item Unit Width	32.3
Item_UOM	pce

Measurements

LENGTH_L	68,2
Length (l1)	28,3
Length (l2)	28,3
z1	11,6

Packaging

Packaging GTIN PL1	06414905635290
Packaging GTIN PL3	06414905635474
Packaging GTIN PL4	06414905499441
Packaging Height PL1	89
Packaging Height PL3	189
Packaging Height PL4	711
Packaging Length PL1	176

Packaging Length PL3	357
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	80
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,018555075
Packaging Volume PL4	0,68256
Packaging Weight PL1	1,224
Packaging Weight PL3	10,312
Packaging Weight PL4	272,488
Packaging Width PL1	135
Packaging Width PL3	275
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb