


Uponor S-Press PLUS tee 32-32-32

1070563

- Made of tin-plated DZR brass



About Uponor S-Press PLUS tee

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS tee 32-32-32

1070563



Product code

Item no EAN	6414905218837
Item no GF	35001070563
Item no GTIN	06414905218837
Item no LVI	1720747
Item no NOBB	55172301
Item no NRF	5114489
Item no RSK	1808009
Item no VVS	045476032

Dimensions

Item Unit Height	70.8
Item Unit Length	102.5
Item Unit Weight	0,34
Item Unit Width	39.3
Item_UOM	pce

Measurements

Length (I1)	51,4
Length (I2)	51,4
Length (I3)	51,4
z1	23
Z2	23
Z3	23

Packaging

Packaging GTIN PL1	06414905283033
Packaging GTIN PL3	06414905424474
Packaging GTIN PL4	06414905283057
Packaging Height PL1	89
Packaging Height PL3	188

Packaging Height PL4	708
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	1,739
Packaging Weight PL3	7,216
Packaging Weight PL4	372
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb