


Uponor S-Press PLUS tee female thread 16-Rp1/2"FT-16

1070595

- Made of tin-plated DZR brass
- Female thread to BS EN 10226-1



About Uponor S-Press PLUS tee female thread

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS tee female thread 16-Rp1/2"FT-16

1070595



Measurements

Female thread Rp	1/2
Length (l1)	38
Length (l2)	33
Length (l3)	38
z1	18,2
Z2	18
Z3	18,2

Product code

Item no EAN	6414905219155
Item no GF	35001070595
Item no GTIN	06414905219155
Item no LVI	1720769
Item no NOBB	55172524
Item no NRF	5114514
Item no RSK	1808031
Item no VVS	045478189

Dimensions

Item Unit Height	43.9
Item Unit Length	76
Item Unit Weight	0,106
Item Unit Width	26
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905468614
Packaging GTIN PL3	06414905424696
Packaging GTIN PL4	06414905499540
Packaging Height PL1	89

Packaging Height PL3	95
Packaging Height PL4	714
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL3	40
Packaging Quantity PL4	3840
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	1,097
Packaging Weight PL3	4,588
Packaging Weight PL4	456
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb