


## Uponor S-Press PLUS adapter swivel nut 25-G1"SN

### 1070607

- Made of tin-plated DZR brass
- Demountable swivel nut for connection to on-wall fittings, equipment, filters and valves
- Thread acc. to BS EN ISO 228-1.



## About Uponor S-Press PLUS adapter swivel nut

### Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

### Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor S-Press PLUS adapter swivel nut 25-G1"SN

1070607



### Measurements

Cylindric_thread_G	1
LENGTH_L	57
Length (l1)	9
Length (l2)	28,3
z1	19,7

### Product code

Item no EAN	6414905219278
Item no GF	35001070607
Item no GTIN	06414905219278
Item no LVI	1720781
Item no NOBB	55172645
Item no NRF	5114527
Item no RSK	1899456
Item no VVS	045483315

### Dimensions

Item Unit Height	39.5
Item Unit Length	47
Item Unit Weight	0,143
Item Unit Width	36
Item_UOM	pce

### Status

MTO (longer delivery times)

Item available on request, minimum lead time 2 weeks

### Packaging

Packaging GTIN PL1	06414905468706
Packaging GTIN PL2	06414905442799
Packaging GTIN PL4	06414905499632
Packaging Height PL1	45

Packaging Height PL2	89
Packaging Height PL4	678
Packaging Length PL1	52
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	15
Packaging Quantity PL4	2880
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00009594
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,144
Packaging Weight PL2	2,24
Packaging Weight PL4	454,08
Packaging Width PL1	41
Packaging Width PL2	135
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)