
Product data sheet



GF Uponor S-Press PLUS adapter 20-22CU

1070617

- Adapter with plated copper spigot
- Connection of the plated copper pipe can be made using standard BS EN 1254-2 compression type fitting,
- or a compatible metal press connection.



About GF Uponor S-Press PLUS adapter

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.


Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval
- WRAS or
- KIWA
to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS adapter 20-22CU

1070617



Product code

Item no EAN	6414905219377
Item no GF	35001070617
Item no GTIN	06414905219377
Item no LVI	1720791
Item no NOBB	55172740
Item no NRF	5114538
Item no RSK	1899442
Item no VVS	045485021

Dimensions

Item Unit Height	26
Item Unit Length	81
Item Unit Weight	0,073
Item Unit Width	26
Item_UOM	pce

Measurements

LENGTH_L	81
Length (l1)	41
Length (l2)	21,3
z1	18,7

Packaging

Packaging GTIN PL1	06414905468775
Packaging GTIN PL3	06414905424788
Packaging GTIN PL4	06414905499700
Packaging Height PL1	89
Packaging Height PL3	95

Packaging Height PL4	714
Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	15
Packaging Quantity PL3	60
Packaging Quantity PL4	5760
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,004710385
Packaging Volume PL4	0,68544
Packaging Weight PL1	1,135
Packaging Weight PL3	4,64
Packaging Weight PL4	469,44
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+