


## Uponor S-Press PLUS adapter 25-28CU

### 1070619

- Adapter with plated copper spigot
- The connection of the plated copper pipe can be made using standard BS EN 1254 compression type fitting, or a compatible metal press connection.



## About Uponor S-Press PLUS adapter

### Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

### Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor S-Press PLUS adapter 25-28CU

1070619



### Product code

Item no EAN	6414905219391
Item no GF	35001070619
Item no GTIN	06414905219391
Item no LVI	1720793
Item no NOBB	55171385
Item no NRF	5114541
Item no RSK	1899444
Item no VVS	045485025

### Dimensions

Item Unit Height	32.3
Item Unit Length	92
Item Unit Weight	0,135
Item Unit Width	32.3
Item_UOM	pce

### Measurements

LENGTH_L	92
Length (l1)	43
Length (l2)	28,3
z1	20,7

### Packaging

Packaging GTIN PL1	06414905468799
Packaging GTIN PL4	06414905499724
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	5

Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,712
Packaging Weight PL4	298,56
Packaging Width PL1	67
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)