


## Uponor S-Press PLUS stop end 20

1070622

- Made of tin-plated DZR brass



### About Uponor S-Press PLUS stop end

#### Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

#### Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor S-Press PLUS stop end 20

1070622



### Product code

Item no EAN	6414905219421
Item no GF	35001070622
Item no GTIN	06414905219421
Item no LVI	1720796
Item no NOBB	55171393
Item no NRF	5114544
Item no RSK	1899447
Item no VVS	045313920

### Dimensions

Item Unit Height	26
Item Unit Length	28
Item Unit Weight	0,035
Item Unit Width	26
Item_UOM	pce

### Measurements

LENGTH_L	28
Length (l1)	6,7
Length (l2)	21,3

### Packaging

Packaging GTIN PL1	06414905635023
Packaging GTIN PL4	06414905499755
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL4	7680

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,738
Packaging Weight PL4	308,392
Packaging Width PL1	67
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)