


Uponor S-Press PLUS U-tap elbow 20-Rp1/2"FT-16

1070631

- For on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



About Uponor S-Press PLUS U-tap elbow

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
- AENOR

Uponor S-Press PLUS U-tap elbow 20-Rp1/2"FT-16

1070631



Technical data

Item (unit of measurement)	pce
Female_thread_Rp	1/2 inch
Length (l1)	57 mm
Length (l2)	56 mm
Length (l3)	20 mm
Z-measurement b	45 mm
Z-measurement k	40 mm
z2	36 mm
z4	8 mm
Packaging Quantity PL1	5
Packaging Quantity PL4	960

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb