

Uponor S-PRESS PLUS elbow adapter 16-12CU l=150mm

1070651

- With plated copper pipe (EN 1057) 15 x 1mm or 12 x 1mm
- Connection of the plated copper pipe can be made using standard BS EN 1254-2 compression type fittings, or a compatible metal press connection.



About Uponor S-PRESS PLUS elbow adapter

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-PRESS PLUS elbow adapter 16-12CU l=150mm

1070651



Product code

Item no EAN	6414905219674
Item no GF	35001070651
Item no GTIN	06414905219674
Item no NOBB	55171438
Item no NRF	5114561
Item no RSK	1896561
Item no VVS	404730126

Dimensions

Item Unit Height	21.9
Item Unit Length	176.6
Item Unit Weight	0,088
Item Unit Width	44.5
Item_UOM	pce

Measurements

Length (l1)	166
Length (l2)	36,5
Z2	16,7

Technical data

Recycling Text Block PL1	Corrugated fibreboard
--------------------------	-----------------------

Status

MTO (longer delivery times) Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1	06414905287048
Packaging GTIN PL4	06414905287055
Packaging Height PL1	185
Packaging Height PL4	699
Packaging Length PL1	185

Packaging Length PL4	1200
Packaging Material (number) PL1	20
Packaging Material PL1	Corrugated fibreboard
Packaging Material (short) PL1	PAP
Packaging Quantity PL1	20
Packaging Quantity PL4	2880
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0031487
Packaging Volume PL4	0,67104
Packaging Weight PL1	1,82
Packaging Weight PL4	286,08
Packaging Width PL1	92
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb