


Uponor S-Press PLUS tap elbow LWC 16-Rp1/2"FT l=35

1070654

- Including twist-proof attachment and sound protection
- For lead-through wall penetrations



About Uponor S-Press PLUS tap elbow LWC

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS tap elbow LWC 16-Rp1/2"FT l=35

1070654



Measurements

Cylindric_thread_G	0,75
Female thread Rp	0,5
Length (l1)	58,5
Length (l2)	46
Z Measurement g	3/4
Z Measurement k	50
z1	19
Z2	26,2

Product code

Item no EAN	6414905219704
Item no GF	35001070654
Item no GTIN	06414905219704

Dimensions

Item Unit Height	78
Item Unit Length	70
Item Unit Weight	0,276
Item Unit Width	65
Item_UOM	pce

Status

MTO (longer delivery times)

Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1	06414905479207
Packaging GTIN PL2	06414905479214
Packaging GTIN PL4	06414905479221
Packaging Height PL1	83
Packaging Height PL2	89
Packaging Height PL4	678

Packaging Length PL1	75
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	5
Packaging Quantity PL4	960
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00043575
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,277
Packaging Weight PL2	1,465
Packaging Weight PL4	305
Packaging Width PL1	70
Packaging Width PL2	135
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb