


## Uponor S-Press PLUS elbow adapter UPS 16-Rp1/2"FT

### 1070657

- Made of tin-plated DR brass



## About Uponor S-Press PLUS elbow adapter UPS

### Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

### Application

- Heating systems (high temperature radiators) - where the water temperature does not continuously exceed 80°C, 10 bar (Conditions to application Class 5 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 100°C for an accumulative 100 hours over the working life of the system. (Heating systems must be installed with room and water temperature controls in accordance with the current Building Regulations Parts L1 (Energy – Dwellings) and L2 (Energy – Non Dwellings) for England and Wales, or an equivalent national standard for Scotland or Republic of Ireland).

- Cold water domestic services: 0°C to 20°C where the water temperature does not exceed 20°C, 16bar.

- Hot water domestic services: 20°C to 70°C where the water temperature does not continuously exceed 70°C, 10 bar (Conditions to application Class 2 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 95°C for an accumulative 100 hours over the working life of the system.

- Uponor multilayer pipe can be used for DHW recirculating systems, provided the operating temperatures and pressures do not exceed the maximum conditions detailed under 'Domestic Services'

- Chilled water: -10°C to 10°C, 10 bar. If risk of damage from freezing, a suitable anti-freeze additive must be used. Any additive must be suitable for use with Polyethylene, PPSU, EPDM and CW625N brass if not different mentioned:

- Male and female threads acc.to EN 10226-1.

### Certification

- WRAS : 1903901 - Uponor S-Press PLUS, S-Press PLUS, PPSU, MLC and SAC 16-32mm

- 2101339 : Manifolds and adapters

- KIWA – UK water Regulation 4

- Manufacturing is in accordance with the international quality standard ISO 9001 and environmental standard ISO 14001.

## Uponor S-Press PLUS elbow adapter UPS 16-Rp1/2"FT

1070657



### Measurements

Female thread Rp 0,5

Metric thread M 35x1,5

### Product code

Item no EAN 6414905219735

Item no GF 35001070657

Item no GTIN 06414905219735

### Dimensions

Item Unit Height 39.9

Item Unit Length 69.5

Item Unit Weight 0,164

Item Unit Width 43

Item\_UOM pce

### Packaging

Packaging GTIN PL1 06414905280803

Packaging GTIN PL2 06414905280810

Packaging GTIN PL4 06414905280827

Packaging Height PL1 45

Packaging Height PL2 89

Packaging Height PL4 678

Packaging Length PL1 75

Packaging Length PL2 176

Packaging Length PL4 1200

Packaging Quantity PL1 1

Packaging Quantity PL2 10

Packaging Quantity PL4 1920

Packaging Type PL1 Plastic\_Bag

Packaging Type PL2 Medium\_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,000162
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,165
Packaging Weight PL2	1,679
Packaging Weight PL4	356,16
Packaging Width PL1	48
Packaging Width PL2	135
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)