

Uponor S-Press PLUS radi elbow adapter plated 25-22CU l=250mm

1070680

- Made of plated brass
- With copper pipe 15 x 1 mm, plated.
- The connection of the plated copper pipe 15 x 1 mm to the radiator can be made using a standard compression fitting



About Uponor S-Press PLUS radi elbow adapter plated

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.
- Unless specified otherwise, male and female threads acc.to EN 10226-1.

Certification

- WRAS
- DVGW
- KIWA

Uponor S-Press PLUS radi elbow adapter plated 25-22CU l=250mm

1070680



Technical data

| | |
|----------------------------|--------|
| Item Quantity 1 | 20 |
| Item Quantity 2 | 640 |
| Item (unit of measurement) | pce |
| Outside diameter | 25 mm |
| Length (l1) | 250 mm |
| Length (l2) | 48 mm |
| z1 | 19 mm |

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb