
Product data sheet



GF Uponor S-Press PLUS radi elbow adapter, plated 25-22CU l=250

1070680

- With plated copper pipe (EN 1057) 15 x 1 mm or 22 x 1 mm
- Connection of the plated copper pipe can be made using a standard BS EN 1254-2 compression type fitting,
- or a compatible metal press connection.



About GF Uponor S-Press PLUS radi elbow adapter, plated

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.


Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval
- WRAS or
- KIWA
to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS radi elbow adapter, plated 25-22CU l=250

1070680



Product code

Item no EAN	6414905219964
Item no GF	35001070680
Item no GTIN	06414905219964
Item no RSK	1896567
Item no VVS	404730025

Dimensions

Item Unit Height	32.3
Item Unit Length	265.8
Item Unit Weight	0,235
Item Unit Width	60.5
Item_UOM	pce

Measurements

Length (l1)	250
Length (l2)	47,5
Z2	19,2

Packaging

Packaging GTIN PL1	06414905427208
Packaging GTIN PL4	06414905427215
Packaging Height PL1	105
Packaging Height PL4	564
Packaging Length PL1	350
Packaging Length PL4	1200
Packaging Quantity PL1	20
Packaging Quantity PL4	640
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00937125
Packaging Volume PL4	0,54144
Packaging Weight PL1	4,902
Packaging Weight PL4	180,864
Packaging Width PL1	255
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+