

## Uponor S-Press PLUS adapter baseboard 16-G1/2"MT-0

1070695

- For baseboard mounting and the universal connection of 16 or 20mm Uponor MLC and Uni-Pipe PLUS pipes to valve
- radiators with bottom connections
- Thread acc. to BS EN ISO 228-1



### About Uponor S-Press PLUS adapter baseboard

#### Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

#### Certification

UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor S-Press PLUS adapter baseboard 16-G1/2"MT-0

1070695



### Measurements

Cylindric_thread_G	0,5
Length (l1)	51
Length (l2)	27,5
Z Measurement b	35
Z Measurement b1	33,8
Z Measurement b2	66,2
z1	31,2

### Product code

Item no EAN	6414905220120
Item no GF	35001070695
Item no GTIN	06414905220120

### Dimensions

Item Unit Height	33.8
Item Unit Length	123.8
Item Unit Weight	0,617
Item Unit Width	113.5
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414905422937
Packaging GTIN PL4	06414905422944
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	192
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,697
Packaging Weight PL4	157,824
Packaging Width PL1	135
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)