Product data sheet



GF Uponor S-Press PLUS adapter baseboard MT 20-G1/2"-20

1070697

- For baseboard mounting and the universal connection of 16 or 20mm Uponor MLC and Uni-Pipe PLUS pipes to valve
- radiators with bottom connections
- Thread acc. to BS EN ISO 228-1



About GF Uponor S-Press PLUS adapter baseboard MT

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification

UK Reg4 approval
- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS adapter baseboard MT 20-G1/2"-20

1070697



Measurements

Cylindric_thread_G	0,5
Length (l1)	52,5
Length (l2)	52,5
Z Measurement b	35
Z Measurement b1	33,8
Z Measurement b2	65
z1	31,2
Z2	31,2

Product code

Item no EAN	6414905220151
Item no GF	35001070697
Item no GTIN	06414905220151

Dimensions

Item Unit Height	33.8
Item Unit Length	123.8
Item Unit Weight	0,659
Item Unit Width	140.2
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905423170
Packaging GTIN PL4	06414905423187
Packaging Height PL1	89
Packaging Height PL4	678
Packaging Length PL1	176
Packaging Length PL4	1200

Packaging Quantity PL1	1
Packaging Quantity PL4	192
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,739
Packaging Weight PL4	165,888
Packaging Width PL1	135
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+