

## Uponor S-Press PLUS adapter 20-15CU

1070707

- Adapter with plated copper spigot
- The connection of the plated copper pipe can be made using standard BS EN 1254 compression type fitting, or a compatible metal press connection.



### About Uponor S-Press PLUS adapter

#### Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

#### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

#### Certification

UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor S-Press PLUS adapter 20-15CU

1070707



### Product code

|              |                |
|--------------|----------------|
| Item no EAN  | 6414905221592  |
| Item no GF   | 35001070707    |
| Item no GTIN | 06414905221592 |
| Item no LVI  | 1720801        |
| Item no NOBB | 55171442       |
| Item no NRF  | 5114564        |
| Item no RSK  | 1899440        |
| Item no VVS  | 045485020      |

### Dimensions

|                  |       |
|------------------|-------|
| Item Unit Height | 26    |
| Item Unit Length | 76    |
| Item Unit Weight | 0,055 |
| Item Unit Width  | 26    |
| Item_UOM         | pce   |

### Measurements

|             |      |
|-------------|------|
| LENGTH_L    | 76   |
| Length (l1) | 39   |
| Length (l2) | 21,3 |
| z1          | 15,7 |

### Packaging

|                        |                |
|------------------------|----------------|
| Packaging GTIN PL1     | 06414905469055 |
| Packaging GTIN PL4     | 06414905499984 |
| Packaging Height PL1   | 89             |
| Packaging Height PL4   | 678            |
| Packaging Length PL1   | 176            |
| Packaging Length PL4   | 1200           |
| Packaging Quantity PL1 | 10             |
| Packaging Quantity PL4 | 3840           |

|                      |             |
|----------------------|-------------|
| Packaging Type PL1   | Base_Box    |
| Packaging Type PL4   | Pallet      |
| Packaging Volume PL1 | 0,001049488 |
| Packaging Volume PL4 | 0,65088     |
| Packaging Weight PL1 | 0,587       |
| Packaging Weight PL4 | 250,56      |
| Packaging Width PL1  | 67          |
| Packaging Width PL4  | 800         |

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)