


Uponor S-Press PLUS adapter swivel nut 16-G3/8"SN

1070708

- Made of tin-plated DZR brass
- Demountable swivel nut for connection to on-wall fittings, equipment, filters and valves
- Thread acc. to BS EN ISO 228-1.



About Uponor S-Press PLUS adapter swivel nut

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS adapter swivel nut 16-G3/8"SN

1070708



Measurements

Cylindric_thread_G	0,375
LENGTH_L	55,4
Length (l1)	8,4
Length (l2)	19,8
z1	27,2

Product code

Item no EAN	6414905221608
Item no GF	35001070708
Item no GTIN	06414905221608
Item no LVI	1720802
Item no NOBB	55172914
Item no NRF	5114565
Item no RSK	1899450
Item no VVS	045483181

Dimensions

Item Unit Height	23.3
Item Unit Length	47.7
Item Unit Weight	0,057
Item Unit Width	21.9
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905469062
Packaging GTIN PL2	06414905442867
Packaging GTIN PL4	06414905499991
Packaging Height PL1	28
Packaging Height PL2	89
Packaging Height PL4	678

Packaging Length PL1	53
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	25
Packaging Quantity PL4	4800
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000040068
Packaging Volume PL2	0,00211464
Packaging Volume PL4	0,65088
Packaging Weight PL1	0,058
Packaging Weight PL2	1,464
Packaging Weight PL4	317,76
Packaging Width PL1	27
Packaging Width PL2	135
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb