


Uponor Ecoflex elbow Rp4-Rp4

1078366

- Parallel thread Rp - requires a suitable sealing medium
- 6 bar, SDR 11 / 10 bar, SDR 7,4
- DZR - dezincification resistant brass



About Uponor Ecoflex elbow

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application


- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex elbow Rp4-Rp4

1078366



Measurements

Female thread Rp	4
Length (l1)	92
Length (l2)	92

Product code

Item no EAN	4021598130258
Item no GF	35001078366
Item no GTIN	04021598130258
Item no LVI	1938511
Item no NOBB	49606934
Item no NRF	8361338
Item no RSK	2282486
Item no VVS	087832016

Dimensions

Item Unit Height	127
Item Unit Length	150
Item Unit Weight	2,65
Item Unit Width	155
Item_UOM	pce

Status

MTO (longer delivery times) Item available on request, minimum lead time 2 weeks

Packaging

Packaging GTIN PL1	06414900328289
Packaging Height PL1	155
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00899

Packaging Weight PL1	2,76
Packaging Width PL1	200

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb