Product data sheet

Uponor Minitec nubfoil self-adh 8pce, 6,2m2 1100x700x12mm

1083866

- Pipe fixation panel made of polystyrol, with overlap on both sides with triangular studs; perforated panel for installation between levelling compound and substructure; with self-adhesive back for proper fixture to screed and tiled floors.



About Uponor Minitec nubfoil self-adh

Specification

- Minitec underfloor heating system for fixation on solid floors or specified insulation materials
- designed as sturdy pipe fixing system of minimum height, with integrated pipe laying channels for correct pipe laying distances
- for use with Uponor Minitec PE-Xa pipes 9.9 x 1.1 mm; allowing for straight and diagonal pipe laying
- EN 13501-1 fire classification: class E.
- standard flammability, building-material class B2, conforming to DIN 4102.
- Pipe spacing: Vz 5, 10, 15
- Net surface with overlapping nubs: 0,77m²

Application

- radiant underfloor heating and cooling
- very low construction height
- for use with qualified filler materials

Certification

- DIN CERTCO: 7F170-F

Product data sheet

Uponor Minitec nubfoil self-adh 8pce, 6,2m2 1100x700x12mm

1083866



Technical data

 Item (unit of measurement)
 set

 Item no VVS
 339262010

 Item no LVI
 2023413

 Item no NRF
 8361056

 Packaging Quantity PL1
 1

 Packaging Quantity PL4
 16

Technical documents



Uponor UK

Blackmor Lane The Pavilion WD18 8GA, Watford UK

T +44 (0)1923 927000 E enquiries.uk@uponor.com

www.uponor.com/en-gb