Product data sheet



GF Uponor Combi Pipe white PN6 32x2,9 50M

1084387

- Operating pressure 6 bar
- Coils
- White



About GF Uponor Combi Pipe white PN6

Specification

- Pipes manufactured from cross-linked polyethylene - PE-Xa acc. BS EN ISO 15875
- Fire class E according to BS EN 13501-1.
- Conduits manufactured from high density polyethylene

- EVOH (ethylene vinyl alcohol) layer for oxygen diffusion resistance as per DIN 4726

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 6 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

- Underfloor heating and low temperature radiators

- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 6 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

GF Uponor Combi Pipe white PN6 32x2,9 50M

1084387



Product code

Item no EAN	6414905514496
Item no GTIN	06414905514496

Dimensions

Item Unit Height	32
Item Unit Length	1000
Item Unit Weight	0,289
Item Unit Width	32
Item_UOM	m

Measurements

Outer Diameter_do	32
Wall thickness_s	2,9

Packaging

Packaging GTIN PL1	06414905417087
Packaging GTIN PL4	06414905430505
Packaging Height PL1	804
Packaging Height PL4	948
Packaging Length PL1	788
Packaging Length PL4	1200
Packaging Quantity PL1	50
Packaging Quantity PL4	300
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,1267104
Packaging Volume PL4	0,91008
Packaging Weight PL1	14,595

Packaging Weight PL4	112,7
Packaging Width PL1	200
Packaging Width PL4	800

Status

Until stocks last	Until stocks last

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+