


Uponor Vario S S manifold FM 3x3/4 Euro

1086539


Uponor Vario S is a stainless steel manifold for use in radiant heating and cooling systems. The 3/4 eurocone connectors allow the connection of all Uponor pipe dimensions. Which makes this manifold universal for Uponor underfloor heating and cooling systems. Comes complete with fill and drain points, 1" swivel connectors and valve pins for actuator control.



No about information

Uponor Vario S S manifold FM 3x3/4 Euro

1086539



Technical data

Item Quantity 1	1
Item Quantity 2	108
Item (unit of measurement)	pce
Cylindric_thread_G	1 inch
Cylindric_thread_G1	3/4 inch
Number of outlets	3 -
pressure	6 bar
Length (l)	260 mm
Length (l1)	87 mm
Length (l2)	73 mm
Z-measurement b	50 mm
Z-measurement b1	215 mm
Z-measurement h	75 mm
Z-measurement h1	30 mm
Z-measurement h2	50 mm
Z-measurement k	185 mm
Z-measurement k1	336 mm
Z-measurement w	357 mm

Technical documents

Download documents here

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb