

Uponor Vario S manifold FM 3x3/4 Euro

1086539

- Supply with flow meter for balancing and shutoff
- Return with valves and caps



About Uponor Vario S manifold FM

Specification

- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold FM 3x3/4 Euro

1086539



Technical data

Item no EAN	4021598135208
Item no GTIN	04021598135208
Item no LVI	2022118
Item (unit of measurement)	pce
Length (l)	260 mm
Length (l1)	87 mm
Length (l2)	73 mm
Z-measurement b	50 mm
Z-measurement b1	215 mm
Z-measurement h	75 mm
Z-measurement h1	30 mm
Z-measurement h2	50 mm
Z-measurement k	185 mm
Z-measurement k1	336 mm
Z-measurement w	357 mm
Packaging Quantity 1	1
Packaging Quantity 4	108
Packaging GTIN PL1	06414905471881
Packaging GTIN PL4	06414905503179
Item Unit Height	357 mm
Item Unit Weight	2,7 kg
Item Unit Width	75 mm

Technical documents

Download documents here

E_enquiries.uk@uponor.com

www.uponor.com/en-gb