
Product data sheet



GF Uponor Smart UFH-pipe 20x2,0 480m

1086578

- UFH pipe made of PE-RT
- Complying with ISO 22391 and fulfils the requirement for oxygen diffusion resistance as per DIN 4726
- Compatible to Uponor Smart compression fittings
- Application class 4
- Design pressure 6 Bar at 70°C



About GF Uponor Smart UFH-pipe

Specification


- Smart underfloor heating system portfolio
- with Tacker panels and pipe fixations

Application

- Underfloor heating systems
- Residential and light commercial heating installations
- Screeded floor constructions with thermal and impact sound insulation

GF Uponor Smart UFH-pipe 20x2,0 480m

1086578



Product code

Item no EAN	7321500058906
Item no GF	35001086578
Item no GTIN	07321500058906
Item no LVI	2022058
Item no NRF	1627397
Item no RSK	2716766
Item no VVS	087414620

Dimensions

Item Unit Height	20
Item Unit Length	1000
Item Unit Weight	0,118
Item Unit Width	20
Item_UOM	m

Status

MTO (longer delivery times)	Item available on request, minimum lead time 2 weeks

Measurements

Outer Diameter_do	20
Wall thickness_s	2

Packaging

Packaging GTIN PL3	06414905284146
Packaging GTIN PL4	06414905284153
Packaging Height PL3	580
Packaging Height PL4	940
Packaging Length PL3	750
Packaging Length PL4	1200

Packaging Quantity PL3	480
Packaging Quantity PL4	960
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL3	0,32625
Packaging Volume PL4	0,9024
Packaging Weight PL3	56,74
Packaging Weight PL4	138,48
Packaging Width PL3	750
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+