

Uponor Smatrix Move PRO humidity sensor S-157

1087160

- room sensor + RH
- measures relative humidity for dew point calculations
- for cooling only and heating and cooling zones
- 3-wire connection to Uponor Smatrix Move PRO controller X-159
- humidity range: 0-100% non-condensing
- accuracy: < 2% RH
- operating voltage: 24V / 50-60 Hz
- operating temperature: -10°C ... +50°C
- protection class: IP20



About Uponor Smatrix Move PRO humidity sensor S-157

Specification

- multi-zone supply water temperature controls
- control up to 4 different supply water temperatures simultaneously
- intelligent auto heating/cooling changeover
- control snow/ice melting systems as well as turf heating
- integration with Smatrix Base PRO room controls possible
- optional connection to BMS via Modbus interface or R-147 KNX gateway (in combination with Smatrix Base PRO only)

Application

- supply water
- commercial buildings
- indoor and outdoor
- radiant heating and cooling
- domestic hot water
- heating only mode
- heating and cooling

Certification

- CE

Uponor Smatrix Move PRO humidity sensor S-157 1087160



Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb