


## Uponor S-Press adapter V 25-22CU-SST

### 1090680

- Made of Gun metal
- Contoured Aluminium-sleeve
- Fast 3-step installation (press without bevel)
- Colour code
- Coupling fit to copper and stainless steel pipes with pressing jaws type V.



## About Uponor S-Press adapter V

### Specification

- with fixed press sleeve
- stop ring
- test safety

### Application

- Heating systems (high temperature radiators) - where the water temperature does not continuously exceed 80°C, 10 bar (Conditions to application Class 5 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 100°C for an accumulative 100 hours over the working life of the system. (Heating systems must be installed with room and water temperature controls in accordance with the current Building Regulations Parts L1 (Energy – Dwellings) and L2 (Energy – Non Dwellings) for England and Wales, or an equivalent national standard for Scotland or Republic of Ireland)

- Cold water domestic services: 0°C to 20°C where the water temperature does not exceed 20°C, 16bar

- Hot water domestic services: 20°C to 70°C where the water temperature does not continuously exceed 70°C, 10 bar (Conditions to application Class 2 - BS EN ISO 21003-1:2008). The maximum short-term malfunction temperature is 95°C for an accumulative 100 hours over the working life of the system.

- Uponor multi-layer pipe can be used for DHW recirculating systems, provided the operating temperatures and pressures do not exceed the maximum conditions detailed under 'Domestic Services'

- Chilled water: -10°C to 10°C, 10 bar. If risk of damage from freezing, a suitable anti-freeze additive must be used. Any additive must be suitable for use with Polyethylene, PPSU, EPDM and CW625N brass

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

### Certification

- WRAS : 2010907 - Uponor S-Press 12 & 14mm, MLC



- WRAS : 2109108 - S-Press & RS Modular 40-110mm, MLC

- KIWA – UK water Regulation 4

- Manufacturing is in accordance with the international quality standard ISO 9001 and environmental standard ISO 14001

## Uponor S-Press adapter V 25-22CU-SST

1090680



### Product code

Item no EAN	6414905221059
Item no GTIN	06414905221059
Item no VVS	045415025
Item Replacement 1	1145405

### Dimensions

Item Unit Height	32
Item Unit Length	64
Item Unit Weight	0,107
Item Unit Width	32
Item_UOM	pce

### Measurements

LENGTH_L	64
Length (I1)	24
Length (I2)	30,4
z1	9,6

### Technical data

Recycling Text Block PL1	Low density polyethylene
Recycling Text Block PL2	Corrugated fibreboard

### Status

MTO (longer delivery times)	Item available on request, minimum lead time 2 weeks
Until stocks last	Until stocks last

### Packaging

Packaging GTIN PL1	06414905268931
Packaging GTIN PL2	06414905270897
Packaging GTIN PL4	06414905276752
Packaging Height PL1	32
Packaging Height PL2	89

Packaging Height PL4	714
Packaging Length PL1	64
Packaging Length PL2	176
Packaging Length PL4	1200
Packaging Material (number) PL1	4
Packaging Material (number) PL2	20
Packaging Material PL1	Low density polyethylene
Packaging Material PL2	Corrugated fibreboard
Packaging Material (short) PL1	LDPE
Packaging Material (short) PL2	PAP
Packaging Quantity PL1	1
Packaging Quantity PL2	5
Packaging Quantity PL4	1920
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000065536
Packaging Volume PL2	0,001049488
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,107
Packaging Weight PL2	0,535
Packaging Weight PL4	230,44
Packaging Width PL1	32
Packaging Width PL2	67
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)