



## Uponor Ecoflex weldable adapter ST PN6 EU 32x2,9-33,7

**1094014**

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



### About Uponor Ecoflex weldable adapter ST PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

#### Certification



UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor Ecoflex weldable adapter ST PN6 EU 32x2,9-33,7

1094014



### Product code

Item no EAN	6414905231720
Item no GF	35001094014
Item no GTIN	06414905231720

### Dimensions

Item Unit Height	51
Item Unit Length	78
Item Unit Weight	0,3
Item Unit Width	62
Item_UOM	pce

### Measurements

LENGTH_L	63
Length (l1)	29
Wall thickness_s	3
Z Measurement d	33,7

### Packaging

Packaging GTIN PL1	06414905278312
Packaging Height PL1	55
Packaging Length PL1	80
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000286
Packaging Weight PL1	0,31
Packaging Width PL1	65

### Technical documents

Download documents here

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)