



## Uponor Ecoflex weldable adapter ST PN6 EU 40x3,7-42,4

**1094015**

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



### About Uponor Ecoflex weldable adapter ST PN6

#### Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

#### Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

#### Certification

- UK Reg4 approval
  - WRAS or
  - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor Ecoflex weldable adapter ST PN6 EU 40x3,7-42,4

1094015



### Product code

Item no EAN	6414905231737
Item no GF	35001094015
Item no GTIN	06414905231737

### Dimensions

Item Unit Height	62
Item Unit Length	75
Item Unit Weight	0,5
Item Unit Width	75
Item_UOM	pce

### Measurements

LENGTH_L	75
Length (l1)	36
Wall thickness_s	3,5
Z Measurement d	42,4

### Packaging

Packaging GTIN PL1	06414905278329
Packaging Height PL1	65
Packaging Length PL1	75
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000365625
Packaging Weight PL1	0,51
Packaging Width PL1	75

### Technical documents

Download documents here

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)