



Uponor Ecoflex weldable adapter ST PN6 EU 40x3,7-42,4

1094015

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



About Uponor Ecoflex weldable adapter ST PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification based on EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers with cylindrical inch male thread
- Max. operating temperature 95°C

Certification



UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex weldable adapter ST PN6 EU 40x3,7-42,4

1094015



Product code

Item no EAN	6414905231737
Item no GF	35001094015
Item no GTIN	06414905231737

Dimensions

Item Unit Height	62
Item Unit Length	75
Item Unit Weight	0,5
Item Unit Width	75
Item_UOM	pce

Measurements

LENGTH_L	75
Length (l1)	36
Wall thickness_s	3,5
Z Measurement d	42,4

Packaging

Packaging GTIN PL1	06414905278329
Packaging Height PL1	65
Packaging Length PL1	75
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000365625
Packaging Weight PL1	0,51
Packaging Width PL1	75

Technical documents

Download documents here

www.uponor.com/en-gb