



Uponor Ecoflex weldable adapter ST PN6 EU 50x4,6-48,3

1094016

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



About Uponor Ecoflex weldable adapter ST PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application

- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification



UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex weldable adapter ST PN6 EU 50x4,6-48,3

1094016



Product code

| | |
|--------------|----------------|
| Item no EAN | 6414905231744 |
| Item no GF | 35001094016 |
| Item no GTIN | 06414905231744 |

Dimensions

| | |
|------------------|-----|
| Item Unit Height | 72 |
| Item Unit Length | 84 |
| Item Unit Weight | 0,7 |
| Item Unit Width | 84 |
| Item_UOM | pce |

Measurements

| | |
|------------------|------|
| LENGTH_L | 84 |
| Length (l1) | 36 |
| Wall thickness_s | 4,15 |
| Z Measurement d | 48,3 |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL1 | 06414905278336 |
| Packaging Height PL1 | 75 |
| Packaging Length PL1 | 85 |
| Packaging Quantity PL1 | 1 |
| Packaging Type PL1 | Plastic_Bag |
| Packaging Volume PL1 | 0,000541875 |
| Packaging Weight PL1 | 0,71 |
| Packaging Width PL1 | 85 |

Technical documents

Download documents here

www.uponor.com/en-gb