



Uponor Ecoflex weldable adapter ST PN6 EU 63x5,8-60,3

1094017

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



About Uponor Ecoflex weldable adapter ST PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex weldable adapter ST PN6 EU 63x5,8-60,3

1094017



Product code

Item no EAN	6414905231751
Item no GF	35001094017
Item no GTIN	06414905231751

Dimensions

Item Unit Height	89
Item Unit Length	87
Item Unit Weight	1
Item Unit Width	102
Item_UOM	pce

Measurements

LENGTH_L	88
Length (l1)	46
Wall thickness_s	4
Z Measurement d	60,3

Packaging

Packaging GTIN PL1	06414905278343
Packaging Height PL1	89
Packaging Length PL1	89
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000807942
Packaging Weight PL1	1,01
Packaging Width PL1	102

Technical documents

Download documents here

www.uponor.com/en-gb