



Uponor Ecoflex weldable adapter ST PN6 EU+GOST 90x8,2-88,9

1094019

- Connection of PE-Xa pipes
- 6 bar, SDR 11
- Steel adapter for welding



About Uponor Ecoflex weldable adapter ST PN6

Specification

- Wipex fittings in corrosion-resistant brass, dezincification to BS EN ISO 6509 with stainless steel screw.
- Sizes 25-110mm, O-ring sealing between Wipex coupling and base fitting
- Sizes 125-160mm, threads must be sealed using a suitable sealing medium
- Bolt set for couplers in stainless steel with brass washer
- Pre-open sleeve design with assembled support part for the dimension 63-110mm.

Application



- Fittings for pipe systems Thermo, Aqua, Quattro, Supra, Supra PLUS and Thermo HP
- Connection of PE and PE-Xa carrier pipes to couplers
- Parallel G male thread
- Max. operating temperature 95°C

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex weldable adapter ST PN6 EU+GOST 90x8,2-88,9

1094019



Product code

Item no EAN	6414905231775
Item no GF	35001094019
Item no GTIN	06414905231775

Dimensions

Item Unit Height	128
Item Unit Length	108
Item Unit Weight	2,3
Item Unit Width	140
Item_UOM	pce

Measurements

LENGTH_L	108
Length (l1)	58
Wall thickness_s	5
Z Measurement d	88,9

Packaging

Packaging GTIN PL1	06414905278367
Packaging Height PL1	130
Packaging Length PL1	110
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,002002
Packaging Weight PL1	2,31
Packaging Width PL1	140

Technical documents

Download documents here

www.uponor.com/en-gb