

Uponor Fluvia pump Wilo Para SC 6m, 130mm

1095112

- Wilo pump 130mm for pump group MPG UK
- Wilo pump 180mm for pump groups CPG



About Uponor Fluvia pump Wilo Para SC

Specification

- Pre-mounted
- Fluvia Move pump groups with supply temperature controller Uponor Smatrix Move
- Fluvia T can be installed with brackets left or right on the installation

Application

- Max. primary temperature: 90°C
- Max. secondary temperature: 55 - 60°C

Uponor Fluvia pump Wilo Para SC 6m, 130mm

1095112



Measurements

Cylindric_thread_G	1
LENGTH_L	139
Length (l1)	130
Z Measurement b1	47
Z Measurement b2	47
Z Measurement h1	34
Z Measurement h2	93

Product code

Item no EAN	6414905427994
Item no GTIN	06414905427994
Item no LVI	2025038
Item no VVS	466261830

Dimensions

Item Unit Height	95
Item Unit Length	130
Item Unit Weight	1,6
Item Unit Width	95
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414905429288
Packaging GTIN PL4	06414905429295
Packaging Height PL1	115
Packaging Height PL4	1500
Packaging Length PL1	235
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	21

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00481045
Packaging Volume PL4	1,44
Packaging Weight PL1	1,65
Packaging Weight PL4	59,65
Packaging Width PL1	178
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb