


## Uponor Ecoflex VIP Thermo Single 75x6,8/140

1095717

- Heating and Cooling
- Single PE-Xa carrier pipe with oxygen barrier, SDR 11
- Max. load 6 bar / 80°C
- VIP + PEX foam, HDPE casing



### About Uponor Ecoflex VIP Thermo Single

#### Specification

- Highest thermally efficient VIP (Vacuum Insulated Panel)  
 $\lambda$  0.004 w\*m/K
- Highest thermal resistance for complete insulation assembly
- Flexible, pre-insulated, self-compensating plastic pipe system manufactured to BS EN 15632 and BS EN 17414.
- Carrier pipe: cross-linked polyethylene (PE-Xa) pipe based on BS EN ISO 15875, natural Coloured, PN 6 (SDR 11)
- Oxygen tightness based on BS EN 15632 to ISO 17455 and DIN 4726
- Insulating material: Revolutionary VIP technology with extremely low lambda value in combination with permanently elastic closed-cell PE-X foam
- Casing pipe: UV stabilised, corrugated polyethylene (HDPE)

#### Application


- Ideal for low-carbon heating and cooling technologies
- Buried services for the transport of heating or cooling water.
- Heating operating temperature 80°C based on BS EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of up to 60 tons

#### Certification

-

## Uponor Ecoflex VIP Thermo Single 75x6,8/140

1095717



### Measurements

Bending radius M	0,6
Outer Diameter_do	140
Outer Diameter_do1	75
Wall thickness_s1	6,8

### Product code

Item no EAN	6414905479160
Item no GF	35001095717
Item no GTIN	06414905479160
Item no LVI	3010238
Item no NRF	8360953
Item no RSK	2266363
Item no VVS	087808275

### Dimensions

Item Unit Height	140
Item Unit Length	1000
Item Unit Weight	2,73
Item Unit Width	140
Item_UOM	m

### Packaging

Packaging GTIN PL1	06414905479702
Packaging Height PL1	2200
Packaging Length PL1	2200
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	7,26
Packaging Weight PL1	546
Packaging Width PL1	1500

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)