


## Uponor RS adapter S-Press PLUS 20-RS2

### 1095818

- Made of tin-plated DZR brass
- Inspection windows on press sleeve
- Press indicator foils
- Fits into all RS2 base parts.



## About Uponor RS adapter S-Press PLUS

### Specification

- Tin-plated brass
- Fixed press sleeve with inspection windows
- Stop ring
- Colour code
- Test safety
- Male and female threads to BS EN 10226-1

### Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

### Certification

UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

## Uponor RS adapter S-Press PLUS 20-RS2

1095818



### Product code

Item no EAN	6414905480111
Item no GF	35001095818
Item no GTIN	06414905480111
Item no LVI	1720835
Item no NRF	5071315
Item no RSK	1899573
Item no VVS	045450320

### Dimensions

Item Unit Height	70
Item Unit Length	61
Item Unit Weight	0,326
Item Unit Width	70
Item_UOM	pce

### Measurements

LENGTH_L	60,9
Length (l1)	20,1
Length (l2)	21,3
z1	19,5

### Packaging

Packaging GTIN PL1	06414905481583
Packaging GTIN PL4	06414905555574
Packaging Height PL1	80
Packaging Height PL4	600
Packaging Length PL1	120
Packaging Length PL4	800
Packaging Quantity PL1	1
Packaging Quantity PL4	378

Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00096
Packaging Volume PL4	0,576
Packaging Weight PL1	0,383
Packaging Weight PL4	164,774
Packaging Width PL1	100
Packaging Width PL4	1200

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)