

Uponor Ecoflex Thermo connection set Twin HP 2x40x3,7-2x32x3,5/175

L=8m

1105780

- A to B connection set include
- Ecoflex Thermo Twin HP heating pipe
- 2 pieces of Quattro rubber end caps
- 4 pieces of Couplings
- 30m of Trench warning tape
- Orders in full pallets



About Uponor Ecoflex Thermo connection set Twin HP

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632 and EN 17414.
- Medium pipe: Cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11), oxygen tightness based on EN 15632.
- Insulating material: Closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- Approvals should be checked by local responsible person

Uponor Ecoflex Thermo connection set Twin HP 2x40x3,7-2x32x3,5/175

L=8m

1105780



Technical documents

Download documents here [↓](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb