

## Uponor Ecoflex Thermo pipe connection set Twin HP 40x3,7/175

**1118631**

- Connection set include:
- 2 pieces of Quattro rubber end caps
- 4 pieces of Couplings
- 30m of Trench warning tape
- box size in table = w,b,h



### About Uponor Ecoflex Thermo pipe connection set Twin HP

#### Specification

- Flexible, pre-insulated, self-compensating plastic pipe system produced based on EN 15632
- Medium pipe: cross-linked polyethylene (PE-Xa) pipe based on EN ISO 15875, natural coloured, PN 6 (SDR 11) or PN 10 (SDR 7,4), Oxygen tightness based on EN 15632
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

#### Application

- Transport of heating and cooling water for buried installations.
- Heating operating temperature 80°C based on EN 15632
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

#### Certification

- Approvals should be checked by local responsible person

## Uponor Ecoflex Thermo pipe connection set Twin HP 40x3,7/175

1118631



### Technical data

Item no EAN	6414905542543
Item no GTIN	06414905542543
Item no VVS	087883540
Item no NRF	8361446
Item (unit of measurement)	set
Packaging Quantity 1	1
Packaging GTIN PL1	06414905542949
Item Unit Height	200 mm
Item Unit Weight	3,48 kg
Item Unit Width	198 mm

### Technical documents

[Download documents here](#)

#### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)