
Product data sheet



GF Uponor S-Press PLUS sliding coupling 32-32

1118709

- Connection of static pipes
- For in-line repairs of Uni-Pipe PLUS & MLC
- Made of tin-plated DZR brass
- With elongated press sleeve



About GF Uponor S-Press PLUS sliding coupling

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.


Certification

UK Reg4 approval
- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

GF Uponor S-Press PLUS sliding coupling 32-32

1118709



Product code

Item no EAN	6414905554935
Item no GF	35001118709
Item no GTIN	06414905554935
Item no LVI	1720839
Item no NRF	5071369
Item no RSK	1899733
Item no VVS	045484332

Dimensions

Item Unit Height	40
Item Unit Length	116
Item Unit Weight	0,335
Item Unit Width	40
Item_UOM	pce

Measurements

LENGTH_L	116
Length (l1)	28
Length (l2)	28
z1	60

Packaging

Packaging GTIN PL1	06414905559862
Packaging GTIN PL3	06414905559879
Packaging GTIN PL4	06414905559886
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	708

Packaging Length PL1	176
Packaging Length PL3	277
Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00211464
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,67968
Packaging Weight PL1	1,7
Packaging Weight PL3	6,8
Packaging Weight PL4	325
Packaging Width PL1	135
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+