


Uponor Ecoflex VIP Aqua Twin 32x4,4-20x2,8/140

1119054

- Warm tap water
- One medium pipe PE-Xa, SDR 7,4
- Max. load 10 bar / 70°C
- Coloured centre profile to identify flow and return lines
- VIP + PEX foam, HDPE casing



About Uponor Ecoflex VIP Aqua Twin

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system.
- Medium pipe: cross-linked polyethylene (PE-Xa) manufactured to BS EN ISO 15875, natural coloured, PN 10 (SDR 7,4)
- Insulating material: Revolutionary VIP technology with extremely low lambda value in combination with permanently elastic closed-cell PE-X foam.
- Casing pipe: UV stabilised, corrugated polyethylene (HDPE)
- Twin pipe: colour coded identification to identify supply and return lines

Application


- Buried installations for the transport of warm tap water
- Tap water operating temperature 70°C based on BS EN ISO 15875
- Malfunction temperature 95°C
- Static verification for heavy traffic load of 60 tons

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex VIP Aqua Twin 32x4,4-20x2,8/140

1119054



Measurements

Bending radius M	0,7
Outer Diameter_do	140
Outer Diameter_do1	32
Outer Diameter_do2	20
Wall thickness_s1	4,4
Wall thickness_s2	2,8

Product code

Item no EAN	6414905556366
Item no GF	35001119054
Item no GTIN	06414905556366
Item no LVI	3010300
Item no NRF	8360972
Item no RSK	2266380
Item no VVS	087364232

Dimensions

Item Unit Height	140
Item Unit Length	1000
Item Unit Weight	1,88
Item Unit Width	140
Item_UOM	m

Packaging

Packaging GTIN PL1	06414905557936
Packaging Height PL1	2200
Packaging Length PL1	2200
Packaging Quantity PL1	200
Packaging Type PL1	Coil
Packaging Volume PL1	7,26

Packaging Weight PL1

376

Packaging Width PL1

1500

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb