

Uponor Ecoflex Supra PLUS con. and end set 90+110/200

1120128

- Connection and end set for Supra PLUS pipe
- Unit controls max.150m frost protection cable
- Controller with 10m sensor cable
- Set 1
- Electrical parts for supply cable
- frost protection cable joint and cable end termination
- Two rubber end caps



About Uponor Ecoflex Supra PLUS con. and end set

Specification

- Flexible, pre-insulated, self-compensating plastic pipe system
- Medium pipe: Polyethylene PE80, PN 12,5 (SDR 11) or PE100, PN 16 (SDR 11) black with blue stripes or PE 100, PN 16 (SDR 11) black with blue layer and new in PE100 RC, PN16 (SDR11) black with blue stripes
- Cable: self-regulating frost protection cable, nominal power output 10W/m at 5°C, electricity feed from one supply point, max.150 m
- Conduit pipe: PE tube to insert a sensor and to measure the temperature
- Insulating material: closed-cell PE-X foam, permanently elastic, ageing-resistant
- Casing pipe: Corrugated polyethylene (HDPE)

Application

- Transport of cold potable water or pressure drainage in situations where there is a risk of freezing
- For buried installations.
- Operating temperature +20°C
- Static verification for heavy traffic load of 60 tons

Certification

- UK Reg4 approval
 - WRAS or
 - KIWA
- To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Ecoflex Supra PLUS con. and end set 90+110/200

1120128



Product code

Item no EAN	6414905633234
Item no GF	35001120128
Item no GTIN	06414905633234
Item no LVI	1844030
Item no NRF	8360727
Item no RSK	2407845
Item no VVS	070699891

Dimensions

Item Unit Height	140
Item Unit Length	380
Item Unit Weight	1,555
Item Unit Width	280
Item_UOM	set

Packaging

Packaging GTIN PL1	06414905641154
Packaging Height PL1	145
Packaging Length PL1	390
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0163995
Packaging Weight PL1	1,815
Packaging Width PL1	290

Technical documents

Download documents here

E
customerservice.uk.bfs@georgfi
scher.com