

Uponor Fluvia Pump IMP NMT mini 15/70-130

1134170

- For pump groups: Push 23, MPG and KRS 6



About Uponor Fluvia Pump IMP NMT mini

Specification

- Pre-mounted
- Fluvia Move pump groups with supply temperature controller Uponor Smatrix Move
- Fluvia T can be installed with brackets left or right on the installation

Application

- Max. primary temperature: 90°C
- Max. secondary temperature: 55 - 60°C

Uponor Fluvia Pump IMP NMT mini 15/70-130

1134170



Product code

Item no EAN	6414900480000
Item no GTIN	06414900480000
Item no NRF	8362677

Dimensions

Item Unit Height	128
Item Unit Length	130
Item Unit Weight	1,8
Item Unit Width	90
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900480017
Packaging Height PL1	200
Packaging Length PL1	200
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,004
Packaging Weight PL1	2
Packaging Width PL1	100

Technical documents

Download documents here

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb