


Uponor Uni Pipe PLUS clip double 20

1135509

- Easy to open clip
- Clips can be assembled in series
- Fixing using screws - max. diameter 5mm



About Uponor Uni Pipe PLUS clip double

Specification

Uponor Uni Pipe PLUS Seamless Aluminium Composite (SAC).

PE-RT/AL/PE-RT - 5 layer composite pipe consisting of an Aluminium pipe (100% oxygen-proof diffusion barrier, exceeding the requirements of DIN 4726), bonded to an inner layer of PE-RT (Polyethylene Raised Temperature), and outer layer of white PE-RT (Polyethylene Raised Temperature)

- Manufactured to BS EN ISO 21003-1 2008.
- Pipes are marked at 1m intervals with full production data in accordance with the requirements of the standard.
- Sizes 14-32 mm supplied as flexible coils
- Sizes 16-32 mm as extra rigid straight lengths.

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

To meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor Uni Pipe PLUS clip double 20

1135509



Measurements

Distance center center	41
Inner_diameter_di	20
LENGTH_L	86
Z Measurement b	18
Z Measurement h	59

Product code

Item no EAN	6414900368223
Item no GTIN	06414900368223

Dimensions

Item Unit Height	18
Item Unit Length	86
Item Unit Weight	0,018
Item Unit Width	59
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900423410
Packaging GTIN PL3	06414900423564
Packaging GTIN PL4	06414900423717
Packaging Height PL1	155
Packaging Height PL3	360
Packaging Height PL4	1980
Packaging Length PL1	225
Packaging Length PL3	485
Packaging Length PL4	1200
Packaging Quantity PL1	40
Packaging Quantity PL3	320
Packaging Quantity PL4	8000

Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00592875
Packaging Volume PL3	0,058491
Packaging Volume PL4	1,9008
Packaging Weight PL1	0,74
Packaging Weight PL3	6,1
Packaging Weight PL4	177,5
Packaging Width PL1	170
Packaging Width PL3	335
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb